Searching PAJ Page 1 of 2



(11)Publication number:

05-017727

(43) Date of publication of application: 26.01.1993

(51)Int.CI.

C09.J C09J 7/02 // H01B

(21)Application number : 03-195745

(71)Applicant: TOPPAN PRINTING CO LTD

TOYO INK MFG CO LTD

(22) Date of filing:

10.07.1991

(72)Inventor: HOTTA KOICHI

NAKAJIMA MASAO

HACHITANI HISAHIRO

(54) FLAME-RETARDANT TAPE

(57) Abstract:

PURPOSE: To provide a flame-retardant tape excellent in flame retardancy, adherability and the storage stability in rolled state, also easy to produce.

CONSTITUTION: A composition prepared by incorporating (A) 100 pts.wt. of an adhesive comprising A1: 10-45 pts.wt. of a copolyester resin, -15 to 10°C in glass transition point and 30-50°C in softening point, A2: I-20 pts.wt. of a second copolyester resin, -30 to -5°C in glass transition point and 90-120°C in softening point, A3: 20-65 pts.wt. of a flame retarder, and A4: 1-10 pts.wt. of silica with (B) 1-3 pts.wt. of a compound having two or more isocyanate (e.g. hexamethylene diisocyanate) as curing agent and (C) 5-25 pts.wt. of titanium dioxide, is applied on a base material sheet to form an adhesive layer, thus obtaining the objective tape.

LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]